



AD 607245



DAVIDSON LABORATORY

DDC



DDC-IRA B

2 OF 3
COPY \$5.00
MICHE \$.100

182p

REPORT 1035



**STEVENS INSTITUTE
OF TECHNOLOGY**

**CASTLE POINT STATION
HOBOKEN, NEW JERSEY**

ESTIMATION OF STABILITY DERIVATIVES AND INDICES
OF VARIOUS SHIP FORMS, AND COMPARISON
WITH EXPERIMENTAL RESULTS

by

Winnifred R. Jacobs

September 1964



R-1035

DAVIDSON LABORATORY
REPORT 1035

September 1964

ESTIMATION OF STABILITY DERIVATIVES AND INDICES
OF VARIOUS SHIP FORMS, AND COMPARISON
WITH EXPERIMENTAL RESULTS

by

Winnifred R. Jacobs

Prepared for
Bureau of Ships Fundamental Hydromechanics
Research Program (S-R009-01-01)
Administered by David Taylor Model Basin
Contract Nonr 263(57)
DL Project 2803/063

Reproduction in whole or in part is permitted
for any purpose of the United States Government.

Approved

A handwritten signature in black ink, reading "Stavros Tsakonas". The signature is written in a cursive style with a long horizontal flourish at the end.

Stavros Tsakonas, Chief
Fluid Dynamics Division

ix + 23 pp.
4 figures
6 appendices (11 tables, 62 figures)

ABSTRACT

The analytical method of Ref. 1 for estimating stability derivatives, and hence stability on course, which combines Albring's empirical modifications of simplified flow theory with low aspect-ratio wing theory, is extended to take into consideration the effects on course stability of higher aspect-ratio fins as well. The method, which had been applied in the earlier report to a family of eight hulls of 0.5 block coefficient, is tested further by application to eight Series 60 forms differing in block coefficient as well as in beam, draft, and displacement — with and without rudders; to an extreme vee modification of a Series 60 model; and to three other forms — a Mariner Class model, a destroyer, and a hopper dredge. Comparison with experimental results shows that the values of stability derivatives and indices determined by the analytical method are of the right orders of magnitude and indicate correct trends. Application to a variety of ship forms has demonstrated that the method can predict relative effects of changes in the geometry of a ship form, as well as the effects of changes in skeg and rudder area.

Keywords: Hydrodynamics, Maneuvering,
Controllability

TABLE OF CONTENTS

Abstract	iii
Nomenclature	vii
Introduction	1
The Analytical Method	4
Assumed Stability Derivatives for Hulls without Deadwood or Fins	4
Assumed Stability Derivatives for Hulls with Large Areas of Deadwood Aft	7
Changes in Stability Derivatives Due to Adding or Subtracting Fins of Aspect Ratio Equal to or Greater than Unity	9
The Stability Indices	10
Presentation and Discussion of Results	13
840 Series Hulls	13
Series 60 Hulls	14
Extreme Vee Modification	15
Mariner Class Hull	16
Destroyer Model	16
Hopper-Dredge Models	17
Course Stability Dependence on Hull Geometry	17
Conclusion	20
References	22
Figures (1 through 4)	
Appendix A - 840 Series Hulls	
Appendix B - Series 60 Hulls	
Appendix C - Extreme Vee Modification of Series 60 Model 1 developed at the University of Michigan	
Appendix D - Mariner Class Hull	
Appendix E - Destroyer Model	
Appendix F - Hopper-Dredge Models	

NOMENCLATURE

A	profile area of wing or hull, ft^2
AR	aspect ratio of wing
B	beam, ft
b	local beam, ft
C_L	lift coefficient based on profile area
C_s	two-dimensional lateral added mass coefficient (sectional inertia coefficient)
\bar{C}_s	average C_s over the hull
$D'_o = \frac{R_f + R_r}{\frac{\rho}{2} U^2 lH}$	total resistance coefficient of the hull
F	force, lb
$F'_y = \frac{F_y}{\frac{\rho}{2} U^2 lH}$	measured lateral force coefficient
g	acceleration of gravity
H	maximum draft, ft
h	local draft, ft
h_f	maximum fin height, ft
I_o	moment of inertia of hull, lb-ft-sec^2
I_z	added moment of inertia of entrained water (see text), lb-ft-sec^2
k_1	Lamb's coefficients of accession to inertia; longitudinal, lateral, and rotational
k_2	
k'	

L	lift, lb
$L' = \frac{L}{\frac{\rho}{2} U^2 l H}$	lift coefficient based on area $l \cdot H$
l	length, ft
$m_0 = \frac{\Delta}{g}$	mass of hull, slugs
$m'_0 = \frac{m_0}{\frac{\rho}{2} l^2 H}$	hull mass coefficient
$m'_1 = k_1 m'_0$	longitudinal added mass coefficient
m'_2	lateral added mass coefficient (see text)
$m'_x = m'_0 + m'_1$	longitudinal virtual mass coefficient
$m'_y = m'_0 + m'_2$	lateral virtual mass coefficient
m'_z	rotational added mass coefficient (see text)
N	yawing moment, lb-ft
$N' = \frac{N}{\frac{\rho}{2} U^2 l^2 H}$	yawing moment coefficient
$n'_z = \frac{I_0 + I_z}{\frac{\rho}{2} l^4 H}$	virtual moment of inertia coefficient
R	radius of turning circle, ft
R_f	frictional resistance, lb
R_r	residual resistance, lb
$r' = \frac{l}{R}$	dimensionless angular velocity
$s = \frac{Ut}{l}$	dimensionless distance along the path of the center of gravity of the hull
t	time, sec
U	velocity of the center of gravity of the hull, ft/sec

x, y, z	coordinate axes fixed in the hull with origin at the center of gravity
\bar{x}	longitudinal distance from LCG, of center of gravity of lateral added mass, ft
x_p	longitudinal distance from LCG, of center of pressure at which lateral force Y acts, ft
x_s	assumed longitudinal distance from LCG, of center of pressure of tail surface or skeg, ft
x_s, x_b	x-coordinates of stern and bow, respectively
Y	lateral hydrodynamic force, lb
$Y' = \frac{Y}{\frac{\rho}{2} U^2 l_H}$	lateral hydrodynamic force coefficient
β	yaw angle or drift angle
δ	rudder angle
Δ	displacement of hull, lb; also increment
ρ	mass density of the fluid, slugs/ft ³
σ_1, σ_2	stability indices

Subscripts (other than those in above definitions)

f	refers to high aspect-ratio fin (skeg or rudder)
H	refers to bare hull
i	refers to ideal fluid
r'	refers to derivative with respect to r'
s	refers to derivative with respect to s
β	refers to derivative with respect to β

BLANK PAGE

INTRODUCTION

In an earlier report,¹ an analytical method was developed for estimating the first-order stability derivatives (static and rotary lateral-force and yawing-moment rates) which would indicate the course stability and turning or steering qualities of ships. The method was applied to the case of a family of eight hulls of the same length and the same prismatic and block coefficient, but differing in draft, beam, and displacement. The hulls were the 840 Series of the Taylor Standard Series type with the after deadwood (faired-in skeg) removed. Experimentally measured lateral forces and yawing moments, from Davidson Laboratory rotating-arm tests at different turning radii, were available for these hulls and for three of the hulls with flat-plate skegs in the place of the removed deadwood.*

Although the analytical method is based upon simple concepts combining simplified flow theory with low aspect-ratio wing theory and using Albring's³ empirical modifications for viscous flow, good correlation was attained between the stability derivatives calculated by this method and those determined from experimental data. However, Albring's modification of the rotary moment rate is a function of prismatic coefficient and, since all the hulls of the 840 Series have the same prismatic (0.54), this modification was not fully tested. It was decided, therefore, to extend application of the prediction method to hulls of other prismatic, with and without skegs or deadwood aft, for which experimental data were available.

Fortunately, straight-course and rotating-arm model tests have been concluded on eight members of the Series 60 family of ships,⁴ so that the effects on stability of varying block and prismatic coefficients, beam,

*Results of several straight-course tests² confirmed previous experience at Davidson Laboratory that entirely reliable static force and moment rates for straight-course motion can be obtained from rotating-arm data at sufficiently large turning radii.

and draft — other form characteristics remaining constant — can be ascertained from the experimental measurements, for comparison with theoretical predictions. These forms were not altered, as were the Standard Series types, by removal of the after deadwood. Tests were made with and without rudder and propeller, and one model was tested with three rudders of differing chord length. In addition, the analytical method was applied to the following four forms: an extreme vee modification of a Series 60 ship,⁴ a mariner class vessel,⁵ and the widely different destroyer⁶ and hopper-dredge⁷ forms. Consistent experimental techniques have been used in tests of these forms conducted in recent years at Davidson Laboratory.

With the exception of the hopper dredge, all models had large areas of deadwood (faired-in skeg, including rudder) aft, with maximum height at the stern from extended keel line to load waterline. The aspect ratio of the skeg, equal to the square of the maximum skeg height divided by the skeg area and doubled to take into account the free-surface effect, was, in all these cases, less than unity. The hopper dredge, on the other hand, had a skeg of small area at the stern, masked from the water surface by the broad bottom of the afterbody. The aspect ratio of this skeg, equal to the square of its maximum height divided by its area, was greater than unity. For this form, and for the Series 60 cases where the rudder was removed or rudder area was added, the effects of altering a body by adding or subtracting area having fin effect could not be treated by using low aspect-ratio wing theory.

The method of Ref. 1 was therefore extended by including the technique of Ref. 8 in studying the effect on ship behavior of adding or subtracting fins. The lift on the fin itself is calculated by using aerodynamic wing theory for wings of aspect ratio greater than unity. Then, by assuming that the interference between fin and body is negligible, as in the simplified theory used in Ref. 1, the changes in static and rotary force and moment rates are computed.

Comparison with experimentally derived stability derivatives and indices shows that the theoretically determined values are of the right orders of magnitude and indicate correct trends. The fact that the analytical method has the ability to predict relative effects of changes in

the geometry of a ship form, in addition to the effects of changes in rudder and skeg area, makes it an acceptable working tool in designing ships for greater course stability. It is useful not only as an augment to experimentation but also in planning an efficient program of model testing.

This project was sponsored by the Office of Naval Research under Contract Nonr 263(57) and technically administered by David Taylor Model Basin.

THE ANALYTICAL METHOD

Assumed Stability Derivatives for Hulls
Without Deadwood or Fins

In the potential flow theory the hydrodynamic force and moment rate coefficients, or stability derivatives, of an elongated body of revolution without appendages are defined for the linearized region of small angles of attack and large radii of rotation as:

On straight course, $r' = \frac{\dot{L}}{R} = 0$.

$$L'_{\beta_H} = Y'_{\beta_H} = 0$$

$$N'_{\beta_H} = m'_2 - m'_1 = N'_{\beta_i} \text{ (Munk ideal moment)}$$

In turn, around $\beta = 0$,

$$Y'_{r_H} = 0$$

$$N'_{r_H} = 0$$

(1)

The notation is that of the Society of Naval Architects and Marine Engineers (see Nomenclature and Fig. 1; the subscript H refers to bare hull). The measured lateral force coefficient is defined as

$$F'_y = Y' - (m'_0 + m'_1) r'$$

and its derivative with respect to r' as

$$\frac{\partial F'_y}{\partial r'} = Y'_{r'} - (m'_0 + m'_1) \quad (2)$$

where m'_0 is the mass coefficient of the hull and m'_1 is the longitudinal added mass coefficient. Lamb,⁹ considering the added mass term as a hydrodynamic force, defines $Y'_{r_H} = -m'_1 = -k_1 m'_0$ where k_1 is the coefficient

of longitudinal accession to inertia (Fig. 2). Equations 1 are equivalent to those derived by Breslin¹⁰ for a long slender body with tapered or pointed ends, from three-dimensional singularity distributions.

In Albring's³ modification of potential flow theory for a body of revolution moving in a viscous and eddying fluid, the lift on the bare hull is no longer zero as in potential theory, but the force developed as by "oblique attack under an angle $[\beta]$ of a correspondingly shaped solid without effect of curvature," which acts at a distance x_p from the center of gravity. In determining this lift force on a surface ship, Ref. 1 follows Fedyaevsky and Sobolev¹¹ in identifying the bare hull of a ship (i.e., the ship without deadwood, ske, or any other area which has only fin effect) with a low aspect-ratio wing. In this analogy the span of the wing is assumed to be double the draft of the ship, to take into account the action of the free water surface. Tsakonas² shows that this "solid wall" method of accounting for free-surface effect is correct for moderate speeds when the influence of wave-making can be neglected.

The dimensionless lift rate per unit lateral area of the hull is assumed as given by Jones' formula for a low aspect-ratio wing, derived from the consideration of elliptic load distributions along the chord and the span of a thin foil. The Jones formula is

$$\frac{\partial C_L}{\partial \beta} = \frac{\pi}{2} AR = \frac{\pi}{2} \left(\frac{2H^2}{A} \right) \quad (3)$$

The total bare-hull lift rate, nondimensionalized on the basis of area $l \times H$, is then

$$L'_{\beta_H} = \frac{\pi H}{l} \quad (4)$$

On combining low aspect-ratio wing theory with Albring's empirically based formulas, the stability derivatives for a bare ship moving in a viscous fluid are obtained as:

On straight course, $r' = l/R = 0$.

The static force rate $Y'_{\beta_H} = L'_{\beta_H} + D'_0 = \frac{\pi H}{l} + D'_0$ (5)

The static moment rate $N'_{\beta_H} = N'_{\beta_i} + \frac{x_p}{l} L'_{\beta_H} = m'_2 - m'_1 + \left(\frac{x_p}{l}\right) \frac{\pi H}{l}$ (6)

In turn, around $\beta = 0$,

The total rotary force rate $\frac{\partial F'_{Y_H}}{\partial r'} = -m'_x + Y'_{r'_H} = -\left(m'_0 + m'_1\right) - \frac{x_p}{l} L'_{\beta_H}$ (7)

The rotary moment rate $N'_{r'_H} = -m'_2 \frac{\bar{x}}{l} - \left(\frac{x_0}{l}\right)^2 L'_{\beta_H}$ (8)

The various terms are determined as follows:

H/l = ratio of maximum draft to length of ship

D'_0 = drag coefficient at yaw angle $\beta = 0$, obtained by experiment or estimated from the Taylor Standard Series curves of resistance¹².

N'_{β_i} = Munk's moment rate in an ideal fluid, equal to the difference between the lateral added mass coefficient m'_2 and the longitudinal added mass coefficient m'_1 of entrained water

x_p = distance from LCG of the center of pressure of lateral force, taken as the center of area of the hull profile (positive if forward of the LCG)

$m'_x = m'_0 + m'_1$ = virtual longitudinal mass coefficient

$m'_0 = \frac{\Delta}{g \frac{\rho}{2} l^2 H}$, where Δ is ship displacement in lb

$m'_1 = k_1 m'_0$, where k_1 is Lamb's coefficient of longitudinal accession to inertia for an equivalent ellipsoid with ratio of minor axis to major axis equal to $2H/l$

$\frac{x_0}{l}$ = half the prismatic coefficient C_p , following Albring

m'_z = the rotary added mass of entrained water acting at the distance \bar{x} from LCG

The terms m'_2 , m'_z , and \bar{x} are estimated as follows, according to the procedure advocated by Martin:¹³

$$m'_2 = \frac{m_2}{\frac{\rho}{2} l^2 H}$$

where

$$m_2 = k_2 \frac{\rho}{2} \pi \int_{x_s}^{x_b} C_s h^2 dx$$

$$m'_z = \frac{k'_z}{k_2} m'_2$$

k_2, k'_z = Lamb's coefficients of accession to inertia, lateral and rotational, for an equivalent ellipsoid (see Fig. 2)

x_s, x_b = x-coordinates of the stern, bow

h = local draft at each section

C_s = two-dimensional lateral added-mass coefficient, determined at each section from the curves on two-dimensional forms of Lewis' sections, by Prohaska¹⁴ (see Fig. 3)

$$\bar{x} = \frac{\int_{x_s}^{x_b} C_s h^2 x dx}{\int_{x_s}^{x_b} C_s h^2 dx} \quad \text{where } x \text{ is positive forward of LCG}$$

Assumed Stability Derivatives for Hulls with Large Areas of Deadwood Aft

For hulls with large areas of deadwood or low aspect-ratio skegs aft, extending to the water surface at the stern, and including rudders

parallel to the center line (rudder angle $\delta = 0$), simplified theory assumes that there is no interference between the bodies and these surfaces, so that the effects of the skeg area are simply additive. The lift rate per unit skeg area is given by Eq.(3) and, as in Ref. 1, the lift is assumed to act at the after end of the skeg, at x_s the distance of the ship stern from the LCG. Since the length of the deadwood, or skeg, plus rudder is small in comparison with the length of the hull, the distance between the stern and the actual center of pressure of the skeg area is a negligible part of the moment arm about the LCG.

The increments due to deadwood, etc., to be added to the bare hull stability derivatives given by Eq.(5)-(8), are (see Ref. 1)

$$\Delta L'_\beta = \Delta Y'_\beta = \frac{\pi H}{l} \quad (9)$$

$$\Delta N'_\beta = \left(\frac{x_s}{l} \right) \frac{\pi H}{l} \quad (10)$$

$$\Delta Y'_{r'} = - \left(\frac{x_s}{l} \right) \frac{\pi H}{l} \quad (11)$$

$$\Delta N'_{r'} = - \left(\frac{x_s}{l} \right)^2 \frac{\pi H}{l} \quad (12)$$

where x_s is negative.

As shown in Ref. 1, these formulas give essentially the same results as those obtained in the procedure suggested by Martin.¹³ Martin modified the linearized equations of motion in the horizontal plane, given in Ref. 15, by including terms involving two-dimensional lateral added mass at the stern to account for the sudden change of section of the hull and skeg at x_s .

The total values of the static and rotary force and moment rates in the case of hulls with large skeg area aft extending to the load waterline at the stern are:

On straight course, $r' = l/R = 0$.

$$Y'_\beta = \frac{2\pi H}{l} + D'_0 \quad (13)$$

$$N'_\beta = m'_2 - m'_1 + \left(\frac{x_p + x_s}{l} \right) \frac{\pi H}{l} \quad (14)$$

In turn, around $\beta = 0$,

$$\frac{\partial F'_y}{\partial r'} = -m'_x - \left(\frac{x_p + x_s}{l} \right) \frac{\pi H}{l} \quad (15)$$

$$N'_r = -m'_z \frac{\bar{x}}{l} - \left(\frac{x_o^2 + x_s^2}{l^2} \right) \frac{\pi H}{l} \quad (16)$$

Changes in Stability Derivatives Due to Adding or Subtracting Fins of Aspect Ratio Equal to or Greater than Unity

In the case of hulls like the hopper dredge, with very little deadwood or skeg area aft (and that masked from the water surface by the hull bottom), a different treatment is required. The bare hull stability derivatives are obtained from Eqs.(5)-(8) as before, but the effect on the derivatives of adding area having fin effect and an aspect ratio which cannot be considered low is determined as in Ref. 8 by using aerodynamic wing theory applicable to wings of higher aspect ratio, equal to or greater than unity. The latter theory is also employed in studying the effects of adding or subtracting rudder area in the hull cases with large deadwood aft.

The dimensionless lift rate per unit of fin area A_f in such case is

$$\frac{\partial C_L}{\partial \beta} = \frac{2\pi}{1 + \frac{2}{AR_f}} \quad (17)$$

Because the skeg or rudder is below the hull bottom and does not extend to the water surface, it is assumed that there are no free-surface effects. Thus the fin aspect ratio AR_f is the ratio of the square of the fin span (maximum height h_f) to the fin area A_f . The increment or decrement to the static-lateral-force rate, nondimensionalized on the basis of area $l \cdot H$, will be

$$\left(\Delta Y'_{\beta}\right)_f = \pm \left(\frac{2\pi}{1 + \frac{2}{AR_f}}\right) \frac{A_f}{\ell H} = \pm \frac{\pi h_f^2}{\ell H} \left(\frac{1}{1 + \frac{AR_f}{2}}\right) \quad (18)$$

where $\left(\Delta Y'_{\beta}\right)_f < 0$ when subtracting fin area.

Again the assumptions are made that interference between fin and body is negligible and that the center of pressure of the fin is at the stern at a distance x_s aft of the LCG. The other stability-derivative changes are then

$$\left(\Delta N'_{\beta}\right)_f = \frac{x_s}{\ell} \left(\Delta Y'_{\beta}\right)_f \quad (19)$$

$$\left(\Delta Y'_{r'}\right)_f = - \frac{x_s}{\ell} \left(\Delta Y'_{\beta}\right)_f \quad (20)$$

$$\left(\Delta N'_{r'}\right)_f = - \frac{x_s^2}{\ell^2} \left(\Delta Y'_{\beta}\right)_f \quad (21)$$

Although Eqs.(19)-(21) are derived for fin area at the stern, they are, through substitution of the correct moment arm in place of x_s , applicable also to added or subtracted fin area at the bow.

In the case of a ship with small skeg of relatively high aspect ratio at the after end of the underwater hull, the stability derivatives Y'_{β} , N'_{β} , $(m'_x - Y'_{r'})$, and $N'_{r'}$ are obtained from Eqs.(5)-(8), modified by Eqs.(18)-(21) with $\left(\Delta Y'_{\beta}\right)_f$ positive. When rudders are removed from hulls with large deadwood area aft, the stability derivatives are defined by Eqs.(13)-(16), modified by Eqs.(18)-(21) with $\left(\Delta Y'_{\beta}\right)_f$ negative.

The Stability Indices

The criteria for inherent dynamic stability of a free body moving on straight course in the horizontal plane are the damping exponents σ_1

and σ_2 in the solution

$$\beta = \beta_1 e^{\sigma_1 s} + \beta_2 e^{\sigma_2 s}, \quad r' = r_1' e^{\sigma_1 s} + r_2' e^{\sigma_2 s}$$

of the homogeneous linearized equations of motion¹⁵

$$\left. \begin{aligned} \left(m'_x - Y'_{r'} \right) r' - m'_y \beta_s - Y'_\beta \beta &= 0 \\ n'_z r'_s - N'_{r'} r' - N'_\beta \beta &= 0 \end{aligned} \right\} \quad (22)$$

Here $s = Ut/\ell$. The damping exponents are given by

$$\sigma_{1,2} = \frac{- \left(n'_z Y'_\beta - m'_y N'_{r'} \right) \pm \sqrt{\left(n'_z Y'_\beta - m'_y N'_{r'} \right)^2 + 4 n'_z m'_y \left[N'_{r'} Y'_\beta + \left(m'_x - Y'_{r'} \right) N'_\beta \right]}}{2 n'_z m'_y} \quad (23)$$

where $m'_x = m'_0 + m'_1$, virtual longitudinal mass coefficient

$m'_y = m'_0 + m'_2$, virtual lateral mass coefficient

$n'_z = \frac{I_0 + I_z}{\frac{\rho}{2} \ell^4 H}$, virtual moment-of-inertia coefficient

$\frac{I_0}{\frac{\rho}{2} \ell^4 H} = \frac{m'_0}{16}$ (assuming the radius of gyration is equal to $\frac{\ell}{4}$)
 = moment of inertia of the ship


$$I_z = k' \frac{\pi \rho}{2} \int_{x_s}^{x_b} C_s h^2 x^2 dx \quad (\text{Ref. 13})$$

= moment of inertia of the entrained mass of water

The derivatives, Y'_β , N'_β , $\left(m'_x - Y'_{r'} \right)$, and $N'_{r'}$, are defined for


the various configurations as follows:

Bare hull (no deadwood)




Eqs.(5)-(8)

Hull with large deadwood and rudder




Eqs.(13)-(16)

Hull with small skeg



Eqs.(5)-(8) plus
Eqs. (18)-(21)

Hull with large deadwood, rudder removed



Eqs.(13)-(16) plus
Eqs.(18)-(21)

The index σ_2 , obtained by using the minus sign in Eq.(23), is always negative. Therefore the stability of the motion depends on the sign of σ_1 or its real part; the more negative σ_1 , the sooner an initial disturbance will damp out, and hence the greater the stability. If σ_1 or its real part is positive, the motion is unstable and the hull cannot be kept on straight course without applying a corrective rudder.

The stability criterion σ_1 is also an index of the turning qualities of a hull in turns that are not too tight, i.e. when nonlinearities can be neglected. A more dynamically stable hull will turn in a larger radius than will a less stable hull with equal rudder force. Conversely, the more stable hull will require greater rudder force than the less stable hull to turn in a given radius. On the other hand, an unstable ship, defined by positive σ_1 , may turn in a direction opposite to that called for by the applied rudder, in which case it will need a large force to bring it around.

PRESENTATION AND DISCUSSION OF RESULTS

In the appendices, lateral-force and yawing-moment coefficients and stability derivatives determined from experimental measurements are compared graphically with those computed by the linear theory of the present report. Annotations pertaining to the appendices follow.

840 Series Hulls

In Appendix A are reproduced the table of particulars and charts of Ref. 1 for three Taylor Standard Series models, with deadwood removed and with flat-plate skegs added in lieu of deadwood. These models had been tested at Davidson Laboratory in 1959 and 1951. The tests were made at Froude numbers of 0.16 and 0.23; hence the assumption that wave-making effects can be neglected is tenable.

Figure A-1 shows the body plan of the parent hull and Fig. A-2 the stern profile with skag installed. Figure A-3 is a summary chart comparing the calculated Y'_β , N'_β , Y'_r , N'_r , and σ_1 with values obtained in 1959 from measurements on the 842 hull,² without skag and with three skegs of different sizes. The calculated and experimentally measured static rates, Y'_β and N'_β , are identical. The calculated and experimental magnitudes of the rotary derivatives and stability index differ slightly, but the stability predictions err on the conservative side.

It is seen that the analytical method predicts the trends in stability derivatives with increase in profile area. This conclusion is confirmed by Figures A-4 and A-5 for the 846 and 848 models, although these models were tested in 1951 by experimental techniques not quite consistent with those of more recent years. As skag area is increased and extended farther aft, Y'_β and Y'_r become more positive, N'_r more negative, and N'_β less positive. All trends are in the direction of greater course stability, as indicated by the progressively more negative value of σ_1 .

Series 60 Hulls

In Appendix B are presented the new results for the eight Series 60 models,⁴ with and without rudder and propeller. The forces and moments are for zero rudder angle and a Froude number of approximately 0.20.

Table B-1 notes the hull particulars and the various coefficients of added mass and center of pressure computed by the present analytical method. Table B-2 gives the stability derivatives estimated from theory, and also those estimated from a "least squares" fit of the experimental data. In the latter procedure the force and moment coefficients are assumed to be of the following polynomial form:

$$\begin{cases} Y' = F_y' + m_o' r' \\ N' \end{cases} = c_0 + c_1 \beta + c_2 r' + c_3 \beta^2 r' + c_4 \beta r'^2 + c_5 \beta^3 + c_6 r'^3 \quad (24)$$

Each model is designated by a sequence of three digits. The first signifies change in hull; the second signifies presence, 1, or absence, 0, of propeller; the third signifies presence, 1, or absence, 0, of design rudder. The digit 2 or 3 in third place refers to rudder with larger or smaller chord, respectively, than the original rudder.

For the models labeled (-,1,1), with rotating propeller and design rudder, Eqs.(13)-(16) are used for the theoretical derivatives with $D_o' = 0$, since the propeller revolutions are adjusted to obtain zero drag condition. The tests of Models 6,1,1 and 7,1,1 in both clockwise and counterclockwise turns showed practically no asymmetry in the data with change in angular velocity from negative to positive. Therefore lift due to propeller operation can be assumed negligible. For models labeled (-,0,0), without propeller or rudder, Eqs.(13)-(16) are modified by Eqs.(18)-(21). In these cases D_o' is the experimentally measured drag coefficient at zero yaw angle. Models 2,1,2 and 2,1,3 with rotating propeller and larger or smaller rudder chord, respectively, than the original 2,1,1 are treated by subtracting the lift due to the original rudder and adding that due to the replacement.

Appendix B includes typical planforms (Figs. B-1,2,3) and a plan of the design rudder in location (Fig. B-4). Figure B-5 is a summary chart for all eight models, with and without rudder and propeller, showing analytically calculated and experimentally derived stability index σ_1 versus ship-mass coefficient $m'_0 = 2 C_B B/l$. Figure B-6 shows σ_1 versus rudder area for Model 2 with rudders of varying chord, again comparing theoretical values with those obtained from a "least squares" fit of the experimental data. The remaining figures (B-7 to B-40) are graphs of lateral-force and yawing-moment coefficients versus yaw angle β and angular velocity r' for individual models, showing the experimental data and values computed on the basis of the linear theory, i.e. first order variation with β and r' .

The correlation between theoretical and experimental derivative estimates is seen to be good for the hulls with rudder and propeller, slightly less good for the hulls without rudder and propeller. The discrepancies are for the most part within the experimental error.

Extreme Vee Modification

Appendix C compares the theoretical and experimental results for an extreme vee modification⁴ of Series 60 Model 1 (Fig. C-1), which was developed at the University of Michigan. Table C-1 tabulates particulars of this hull (Model 9), with and without propeller and design rudder, the calculated added mass and center of pressure coefficients, and the stability index σ_1 as computed from theoretical derivatives and from experimentally measured rates. Figures C-2 to C-5 are graphs of the lateral-force and yawing-moment coefficients for models 9,1,1 and 9,0,0, similar to those for the Series 60 hulls.

While the calculated static and rotary lateral force derivatives apply as well to the experimental data, the discrepancies between calculated and experimentally measured moment derivatives are larger than for the normal Series 60 forms. However, the contrary effects of lower static instability and lower rotary stability, predicted by theory, appear to cancel each other in the calculations of the stability index. The experimental and theoretical estimates of σ_1 are close.

It is suspected that because of the extreme fineness at the bow (the bow sections of the Series 60 model have been pared to fine vee forms while the profile remains the same), there is some vibration at the bow in yawed motion. Such a condition would affect the measured moments.

Mariner Class Hull

Appendix D treats the Mariner class hull (Table D-1, Fig. D-1) reported in Ref. 5. After that note was published, however, it was found that the calibrations used to reduce the test data were in error. The data have since been revised, with correct calibrations, and are shown on Figs. D-2,3,4, for the hull without propeller, with rudder amidship.

The tests had been conducted on the rotating arm at Davidson Laboratory in 1963. The model was run at a Froude number around 0.20, so that for this model, also, the effects of wave-making can be neglected.

The charts show that the theoretical derivatives obtained by using Eqs.(13)-(16) fit the experimental data reasonably well. Table D-2 gives a comparison of the stability derivatives and indices derived here and the results of Ref. 16 as obtained by an oscillator technique.

Destroyer Model

Appendix E presents the results for the DD692 destroyer model (Fig. E-1, Table E-1), with twin rudders and propellers, tested on the rotating arm at Davidson Laboratory⁶ in 1963. The coefficients of measured forces and moments at three turning diameters for zero rudder angle and Froude number of 0.155 are presented in Figs. E-2,3.

Equations (13)-(16) are used for the theoretical derivatives, and it is assumed that the effects of the off-center twin rudders at zero angle and of the propellers are negligible additions to the effect of the skeg at the stern. The calculated static rates on straight course seem reasonable extrapolations of the rotating-arm data. The calculated rotary rates are close to the measured slopes, certainly within the experimental error.

Hopper-Dredge Models

The results for the hopper-dredge model (Fig. F-1 of Appendix F), under two displacement conditions, are presented in Figs. F-2,3,4,5. This model was tested on the rotating arm at Davidson Laboratory in 1960,⁷ at Froude numbers of 0.12 and 0.20 for the heavy displacement case and 0.155 for the light case.

The theoretical derivatives shown on the charts were calculated from Eqs.(5)-(8) for bare hull, modified by Eqs.(18)-(21) for the small skeg-plus-rudder at the stern. The pertinent characteristics of the models are given in Table F-1. Table F-2 compares the theoretical values of stability index σ_1 with those calculated from the measurements and reported in Ref. 7.

Although the theoretical estimates are on the average 18% less than the experimental, both indicate an extremely unstable vessel. The theory and results of this report underline the recommendations of Ref. 7, viz., to increase the deadwood forward of the rudder stock and to increase the chord of the rudder aft for stability.

COURSE STABILITY DEPENDENCE ON HULL GEOMETRY

An analysis of the assumed expressions for ship lateral-force and yawing-moment derivatives will be made in the light of the results presented, to discover the major form-parameters on which course stability depends. It is well known, and further proof has been added here, that low aspect-ratio skegs or deadwood at the afterbody are essential for minimum stability. It has also been demonstrated that increasing skeg area aft by widening the chord of skeg or rudder improves the stability, and that removing area with fin effect at the stern lowers the stability. But aside from such fin areas, how can one tell by the dimensions and body lines of a ship whether the design will lead to greater or less stability? The answer lies in the make-up of the various terms involved in Eqs.(5)-(16). These will be examined now.

For practical ships, the longitudinal coefficient of accession to

inertia k_1 is close to zero, so that the longitudinal added-mass coefficient m_1' is negligible. The lateral and rotational coefficients of accession to inertia, k_2 and k' , are approximately equal, and therefore m_2' can be substituted for m_2' . The virtual moment-of-inertia coefficient n_2' is close to $(m_0' + m_2')/16$ for the variety of hull forms treated here. In general, variations in x_p and \bar{x} (the centers of pressure of the lift and lateral added mass, respectively) and in position of longitudinal center of gravity are minor in their influence on the stability derivatives of hulls with deadwood aft. The lift coefficient varies inversely with length-draft ratio. The less important drag coefficient depends, as is known, on block coefficient and beam-draft ratio, and hence on m_0' , which is a function of block coefficient and beam-length ratio, and on l/H . The major factors influencing the derivatives and stability index σ_1 are thus seen to be m_0' , m_2' , and l/H .

The dependence of σ_1 on x_0/l , which under Albring's assumption is equal to half the prismatic coefficient, is implicit in its dependence on m_0' and m_2' . The ship-mass coefficient is

$$m_0' \equiv 2 C_B \frac{B}{l} \quad (25)$$

The lateral added-mass coefficient formula

$$m_2' = \frac{k_2 \pi}{l^2 H} \int_{x_s}^{x_b} C_s h^2 dx$$

with $k_2 \sim 1$, and $h = H$, maximum draft, for almost the entire length of commercial and naval vessels, can be written approximately as

$$m_2' \approx \frac{\pi H}{l} \bar{C}_s \quad (26)$$

where $\bar{C}_s = \frac{1}{l} \int_{x_s}^{x_b} C_s dx$, an average sectional inertia coefficient for the hull.

C_s is a function of section beam-draft ratio and section-area coefficient, depending more heavily on the latter (see Fig. 3). Thus prismatic, which is the quotient of block coefficient by midship section-area coefficient,

is involved in both m'_0 and m'_2 .

On substituting the approximations noted above in Eq.(23), it can be shown that σ_1 is some function of the inverse of $(m'_0 + m'_2) l/H$. A graph of σ_1 versus $(m'_0 + m'_2) l/H$ for the stable hulls, with low aspect-ratio skegs, or deadwood plus rudder, to the stern, shows clearly that the major form factors have been well explored. On Fig. 4 are plotted the experimentally derived values for hulls tested in recent years at Davidson Laboratory with consistent experimental techniques. The hulls vary in block coefficient from 0.50 to 0.80, in length-draft ratio from 14.5 to 27.40, in length-beam ratio from 6 to 9.45, and in beam-draft ratio from 2.50 to 3.28. The average sectional inertia coefficients \bar{C}_s are tabulated below:

Model	C_B	\bar{C}_s
842	0.50	0.83
Series 60	0.60	1.02
	0.70	1.07
	0.80	1.16
Extreme vee	0.60	0.93
Mariner	0.61	0.92
Destroyer	0.57	0.76

The curve on Fig. 4 is represented by the formula

$$\sigma_1 = - \left[\frac{5H}{(m'_0 + m'_2) l} \right]^{2.5} \quad (27)$$

and is seen to fit the data very well. By making use of Eqs.(25) and (26), course stability is shown to vary inversely as

$$- \left[2 C_B \frac{B}{H} + \pi \bar{C}_s \right]^{2.5}$$

which may be easily computed from the ship lines and with the aid of Fig. 3. This relationship shows that stability will be increased for hulls with low aspect-ratio skegs to the stern by decreasing one or more of these three form factors: block coefficient, beam-draft ratio, and average sectional inertia coefficient.

CONCLUSION

The analytical method of Ref. 1 for estimating force and moment rates in yawing motion and stability on course, which combines Albring's empirical modifications of simplified flow theory with low aspect-ratio wing theory, has been extended here to take into consideration the effects on course stability of higher aspect-ratio fins. The method had been applied in Ref. 1 to eight 840 Series hulls, of 0.5 block coefficient and varying beam, draft, and displacement. The hulls were Taylor Standard Series forms with the after deadwood removed, but three of the hulls had also been tested with low-aspect-ratio flat-plate skegs in the place of the removed deadwood. The extended method has now been applied to 12 other ships: six Series 60 forms of 0.6 block coefficient and varying beam, draft, and displacement; two Series 60 forms of 0.7 and 0.8 block; an extreme vee modification of a Series 60, 0.6 block form; and three other widely different forms — a Mariner Class ship, a destroyer, and a hopper dredge at two displacements. All had large areas of deadwood aft, except the hopper dredge, which had a small skeg at the stern. The Series 60 cases without rudders, and the case of one model with rudders of larger and smaller chord, have also been treated, making 24 cases in all.

Good correlation is shown between the values of stability derivatives calculated by this method and those based on experimental measurements, despite the variety in ship design. It has been shown that low aspect-ratio skegs or deadwood at the afterbody are essential for minimum stability and that additional skeg area or an extension of rudder area aft increases stability. For the stable ship with large skegs to the stern, the major form factors influencing course stability are demonstrated to be the coefficients of ship mass and lateral added mass of entrained water and the length-draft ratio, or, as a corollary, the block coefficient,

beam-draft ratio, and average sectional inertia coefficient. The functional relationship is expressed by the empirical formula

$$\sigma_1 = - \left[\frac{5H}{(m'_0 + m'_2) \ell} \right]^{2.5} \approx - \left[\frac{5}{2 C_B \frac{B}{H} + \pi \bar{C}_S} \right]^{2.5}$$

The results of this report show that the values of stability derivatives and indices determined by the analytical method are of the right orders of magnitude and indicate correct trends. Application to a variety of ship forms has demonstrated that the method can predict relative effects of changes in the geometry of a ship form, as well as the effects of changes in skeg and rudder area. The analytical method has thus been proved an effective tool to be used in designing ships for greater course stability and in planning an economical program of model testing.

REFERENCES

1. JACOBS, W.R., "Method of Predicting Course Stability and Turning Qualities of Ships," DL Report 945, March 1963.
2. TSAKONAS, S., "Effect of Appendage and Hull Form on the Hydrodynamic Coefficients of Surface Ships," DL Report 740, May 1959.
3. ALBRING, W., "Summary Report of Experimental and Mathematical Methods for the Determination of Coefficients of Turning of Bodies of Revolution," CONLAN 2.
4. CRANE, C.L., JR., "Research on Ship Controllability," DL Quarterly Progress Report, 1 June 1964.
5. SUAREZ, A., "Rotating Arm Experimental Study of a Mariner Class Vessel," DL Note 696, June 1963. (Measurements revised using correct calibration, April 1964).
6. SUAREZ, A., DL Confidential Letter Report 1012, February 1964.
7. SUAREZ, A., "Stability Analysis of SS Sandcaptain," DL Letter Report 786, March-May 1960.
8. GIMPRICH, M. and JACOBS, W.R., "The Effect of Fins on the Behavior of Free Bodies," ETT DL Report 361, February 1950. CONFIDENTIAL.
9. LAMB, H., Hydrodynamics, Dover Publications, 6th ed., New York, 1945.
10. BRESLIN, J.P., "Derivation of Slender-Body Approximations for Force and Moment Derivatives from Three-Dimensional Singularity Distributions," DL TM 134, January 1963.
11. FEDYAEVSKY, K.K. and SOBOLEV, G.V., "Application of the Results of Low Aspect-Ratio Wing Theory to the Solution of Some Steering Problems," Proc., Netherlands Ship Model Basin Symposium on the Behavior of Ships in a Seaway, Wageningen, September 1957.
12. GERTLER, M., "A Reanalysis of the Original Test Data for the Taylor Standard Series," DTMB Report 806, March 1954.
13. MARTIN, M., "Analysis of Lateral Force and Moment Caused by Yaw During Ship Turning," DL Report 792, March 1961.
14. PROHASKA, C.W., "The Vertical Vibration of Ships," Shipbuilder and Marine Engine-Builder, October-November 1947.

15. DAVIDSON, K.S.M. and SCHIFF, L.I., "Turning and Course-Keeping Qualities," Transactions SNAME, 1946.
16. PAULLING, J.R. and WOOD, L.W., "The Dynamic Problem of Two Ships Operating on Parallel Courses in Close Proximity," University of California Series No. 189, 18 July 1963.

BLANK PAGE




FIGURE 1. MODEL ORIENTATION IN X-Y PLANE




FIGURE 2. COEFFICIENTS OF ACCESSION TO INERTIA FOR PROLATE SPHEROIDS (FROM H. LAMB'S HYDRODYNAMICS)




FIGURE 3. SECTIONAL INERTIA COEFFICIENTS C_s AS FUNCTIONS OF THE LOCAL BEAM-DRAFT RATIO b/h AND SECTION AREA COEFFICIENT, FROM PROHASKA




FIGURE 4. STABILITY INDEX σ_1 FOR HULLS WITH LOW ASPECT-RATIO SKEGS (DEADWOOD) TO STERN.

R-1035

APPENDIX A

840 SERIES HULLS

(Reference 1)

TABLE A-1
PERTINENT CHARACTERISTICS OF THE 840 SERIES HULLS (Taylor Standard Series)

<u>Model No.</u>	<u>842</u>	<u>846</u>	<u>848</u>
Length l , ft	6.0	6.0	6.0
Beam B , ft	0.870	0.870	0.691
Draft H , ft	0.298	0.188	0.236
Displacement Δ , lb	48.40	30.50	30.50
Prismatic coefficient $C_p (= \frac{2x_0}{l})$	0.54	0.54	0.54
Block coefficient C_B	0.50	0.50	0.50
LCG/ l , from bow	0.520	0.481	0.481
B/H	2.92	4.62	2.92
l/B	6.90	6.90	8.68
l/H	20.13	31.90	25.42

Lamb's Coefficients of Accession to Inertia for Equivalent Ellipsoids

Major axis/minor axis, $l/2H$	10.06	15.95	12.71
k_1 (longitudinal)	.020	.012	.017
k_2 (lateral)	.960	.978	.967
k' (rotational)	.885	.935	.902

Other Physical Characteristics

m_o' , mass coefficient	.145	.145	.115
m_1' , longitudinal added-mass coefficient	.003	.002	.002
m_2' , lateral added-mass coefficient	.129	.084	.103
m_z' , rotational added-mass coefficient	.119	.080	.096
n_z' , virtual moment-of-inertia coefficient	.0165	.0141	.0132
\bar{x}/l , CG of lateral added mass from LCG	.110	.070	.070
x_p/l , center of area of profile from LCG	.091	.052	.052
D_o' (estimated drag coefficient at $\beta = 0$)	.014	.018	.014




FIGURE A-1. BODY PLAN OF MODEL PARENT (840 SERIES)





FIGURE A-2. SKEG 20 INSTALLED ON MODEL




FIGURE A-3. COMPARISON OF CALCULATED AND EXPERIMENTAL STABILITY DERIVATIVES AND INDICES FOR 842 HULL WITH VARIOUS SKEGS




FIGURE A-4. COMPARISON OF CALCULATED AND EXPERIMENTAL STABILITY DERIVATIVES AND INDICES FOR 846 HULL WITH-OUT AND WITH SKEG




FIGURE A-5. COMPARISON OF CALCULATED AND EXPERIMENTAL STABILITY DERIVATIVES AND INDICES FOR 848 HULL WITH-OUT AND WITH SKEG

BLANK PAGE

R-1035

APPENDIX B

SERIES 60 HULLS
(Reference 4)

TABLE B-1
PERTINENT CHARACTERISTICS OF THE SERIES 60 HULLS

Model	1,1,1	2,1,1	2,1,2	2,1,3	3,1,1	4,1,1	5,1,1	6,1,1	7,1,1	8,1,1
Length l , ft (LBP)	5.0	—————→								
Beam B , ft	0.667	0.714	—————→		0.833	0.625	0.714	—————→		
Draft H , ft	0.267	—————→					0.2175	0.345	0.267	—————→
Displacement Δ , lb	33.27	35.63	—————→		41.56	31.19	29.10	46.07	41.64	47.50
Prismatic coefficient, $C_p = 2x_o/l$	0.614	—————→					0.616	0.614	0.713	0.807
Block coefficient C_B	0.6	—————→							0.7	0.8
LCG/ l from bow	0.515	—————→							0.505	0.475
B/H	2.50	2.68	—————→		3.12	2.34	3.28	2.07	2.68	2.68
l/B	7.5	7.0	—————→		6.0	8.0	7.0	7.0	7.0	7.0
l/H	18.75	—————→					23.00	14.50	18.75	—————→
Rudder span, ft	0.200	—————→					0.164	0.258	0.200	0.200
Rudder chord, ft	0.105	0.105	0.167	0.080	0.105	—————→				
<u>Lamb's Coefficients of Accession to Inertia for Equivalent Ellipsoids</u>										
Minor axis/major axis, $2H/l$	0.1067	—————→					0.0870	0.0690	0.1067	—————→
k_1 (longitudinal)	0.022	—————→					0.019	0.033	0.022	—————→
k_p (lateral)	0.957	—————→					0.968	0.940	0.957	—————→
k' (rotational)	0.875	—————→					0.903	0.820	0.875	—————→
<u>Other Physical Characteristics</u>										
m_o' , mass coefficient	0.160	0.171	—————→		0.200	0.150	0.171	0.171	0.200	0.229
m_1' , longitudinal added-mass coefficient	0.003	0.004	—————→		0.004	0.003	0.004	0.006	0.004	0.005
m_2' , lateral added-mass coefficient	0.171	0.170	—————→		0.169	0.172	0.138	0.220	0.180	0.194
m_z' , rotational added-mass coefficient	0.153	0.152	—————→		0.151	0.154	0.127	0.192	0.165	0.175
n_z' , virtual moment-of-inertia coefficient	0.0213	0.0219	—————→		0.0237	0.0206	0.0202	0.0239	0.0237	0.0271
\bar{x}/l , CG of lateral added mass from LCG	0.048	0.049	—————→		0.048	0.049	0.048	0.049	0.039	0.005
x_p'/l , center of area of profile from LCG	0.028	—————→					0.033	0.028	0.026	-0.016
D_o' (estimated drag coefficient at $B=0$)	0.015	—————→		0.017	0.014	0.017	0.015	0.019	0.021	


TABLE B-2
STABILITY DERIVATIVES FOR THE SERIES 60 HULLS

a) Models with Rudder and Propeller*	1,1,1	2,1,1	2,1,2	2,1,3	3,1,1	4,1,1	5,1,1	6,1,1	7,1,1	8,1,1
	<u>Estimated from Theory</u>									
$Y'_B = L'_B$	0.335	0.335	0.347	0.329	0.335	0.335	0.273	0.434	0.335	0.335
N'_B	0.088	0.086	0.080	0.089	0.085	0.089	0.071	0.114	0.097	0.095
$m'_x - Y'_{r1}$	0.083	0.095	0.089	0.098	0.124	0.083	0.110	0.077	0.125	0.140
N'_{r1}	-0.066	-0.066	-0.069	-0.065	-0.066	-0.066	-0.054	-0.081	-0.068	-0.077
σ_1	-0.59	-0.55	-0.64	-0.49	-0.41	-0.61	-0.33	-0.76	-0.35	-0.33
	<u>Estimated from "Least Squares" Fit of Experimental Data</u>									
Y'_B	0.255	0.305	0.311	0.293	0.308	0.283	0.260	0.387	0.335	0.323
N'_B	0.110	0.095	0.081	0.100	0.089	0.091	0.075	0.132	0.096	0.086
$m'_x - Y'_{r1}$	0.040	0.081	0.075	0.089	0.111	0.062	0.077	0.077	0.127	0.125
N'_{r1}	-0.080	-0.070	-0.076	-0.073	-0.075	-0.066	-0.057	-0.081	-0.068	-0.070
σ_1	-0.57	-0.52	-0.62	-0.45	-0.42	-0.56	-0.45	-0.60	-0.34	-0.34

*Propeller revolutions adjusted to obtain zero drag condition.


b) Models without Rudder or Propeller	1,0,0	2,0,0	3,0,0	4,0,0	5,0,0	6,0,0	7,0,0	8,0,0
	<u>Estimated from Theory</u>							
$Y'_B = L'_B + D'_O$	0.303	0.303	0.305	0.302	0.247	0.395	0.306	0.309
N'_B	0.112	0.110	0.109	0.113	0.092	0.140	0.121	0.121
$m'_x - Y'_{r1}$	0.108	0.119	0.148	0.108	0.131	0.103	0.149	0.165
N'_{r1}	-0.055	-0.055	-0.055	-0.055	-0.043	-0.068	-0.056	-0.064
σ_1	-0.20	-0.15	-0.027	-0.20	+0.075	-0.38	+0.32	+0.005
	<u>Estimated from "Least Squares" Fit of Experimental Data</u>							
Y'_B	0.245	0.237	0.260	0.217	0.315	0.287	0.256	
N'_B	0.114	0.134	0.116	0.097	0.140	0.121	0.093	
$m'_x - Y'_{r1}$	0.101	0.134	0.081	0.100	0.103	0.149	0.154	
N'_{r1}	-0.055	-0.054	-0.059	-0.045	-0.068	-0.056	-0.052	
σ_1	-0.09	+0.19	-0.26	0	-0.22	+0.067	+0.033	

BLANK PAGE




MODEL 2
 SERIES 60, $C_B=0.6$
 $B/H=2.68$ $L/H=18.75$

FIGURE B-1. BODY PLAN OF SERIES 60 MODEL 2



MODEL 5
 SERIES 60, $C_b=0.6$
 $B/H=3.28$, $L/H=23.0$

FIGURE B-2. BODY PLAN OF SERIES 60 MODEL 5



MODEL 8
 SERIES 60, $C_B = 0.8$
 $B/H = 2.68$, $L/H = 18.75$

FIGURE B-3. BODY PLAN OF SERIES 60 MODEL 8




FIGURE B-4. SERIES 60, STERN PROFILE OF MODELS 1,2,3,4,7,8 WITH DESIGN RUDDER




FIGURE B-5. STABILITY INDEX σ_1 , FOR SERIES 60 HULLS




FIGURE B-6. STABILITY INDEX σ_1 FOR MODEL 2, SERIES 60, WITH RUDDERS OF VARYING CHORD





FIGURE B-7. SERIES 60, MODEL 1,1,1. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-8. SERIES 60, MODEL 1,1,1. YAWING MOMENT COEFFICIENT





FIGURE B-9. SERIES 60, MODEL 2,1,1. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-10. SERIES 60, MODEL 2,1,1. YAWING MOMENT COEFFICIENT





FIGURE B-11. SERIES 60, MODEL 2,1,2. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-12. SERIES 60, MODEL 2,1,2. YAWING MOMENT COEFFICIENT





FIGURE B-13. SERIES 60, MODEL 2,1,3. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-14. SERIES 60, MODEL 2.1.3. YAWING MOMENT COEFFICIENT




FIGURE B-15. SERIES 60, MODEL 3,1,1. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-16. SERIES 60, MODEL 3.1.1. YAWING MOMENT COEFFICIENT





FIGURE B-17. SERIES 60, MODEL 4,1,1. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-18. SERIES 60, MODEL 4.1.1. YAWING MOMENT COEFFICIENT





FIGURE B-19. SERIES 60, MODEL 5,1,1. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-20. SERIES 60, MODEL 5,1,1. YAWING MOMENT COEFFICIENT





FIGURE B-21. SERIES 60, MODEL 6,1,1. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-22. SERIES 60, MODEL 6.1.1. YAWING MOMENT COEFFICIENT





FIGURE B-23. SERIES 60, MODEL 7,1,1. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-24. SERIES 60, MODEL 7,1,1. YAWING MOMENT COEFFICIENT





FIGURE B-25. SERIES 60, MODEL 8,1,1. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-26. SERIES 60, MODEL 8,1,1. YAWING MOMENT COEFFICIENT




FIGURE B-27. SERIES 60, MODEL 2,0,0. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-28. SERIES 60, MODEL 2,0,0. YAWING MOMENT COEFFICIENT





FIGURE B-29. SERIES 60, MODEL 3,0,0. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-30. SERIES 60, MODEL 3,0,0. YAWING MOMENT COEFFICIENT




FIGURE B-31. SERIES 60, MODEL 4,0,0. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-32. SERIES 60, MODEL 4,0,0. YAWING MOMENT COEFFICIENT





FIGURE B-33. SERIES 60, MODEL 5,0,0. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-34. SERIES 60, MODEL 5,0,0. YAWING MOMENT COEFFICIENT





FIGURE B-35. SERIES 60, MODEL 6,0,0. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-36. SERIES 60, MODEL 6,0,0. YAWING MOMENT COEFFICIENT





FIGURE B-37. SERIES 60, MODEL 7,0,0. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-38. SERIES 60, MODEL 7,0,0. YAWING MOMENT COEFFICIENT





FIGURE B-39. SERIES 60, MODEL 8,0,0. TOTAL LATERAL FORCE COEFFICIENT





FIGURE B-40. SERIES 60, MODEL 8,0,0. YAWING MOMENT COEFFICIENT

R-1035

APPENDIX C

**EXTREME VEE MODIFICATION OF SERIES 60 MODEL 1
DEVELOPED AT THE UNIVERSITY OF MICHIGAN**

(Reference 4)

TABLE C-1

PERTINENT CHARACTERISTICS OF THE EXTREME VEE MODIFICATION
OF SERIES 60 MODEL 1

Model	9,1,1	9,0,0
Length ℓ , ft	5.0	————→
Beam B, ft	0.667	————→
Draft H, ft	0.267	————→
Displacement Δ , lb	33.10	————→
Prismatic coefficient $C_p = 2x_o/\ell$	0.614	————→
Block coefficient C_B	0.6	————→
LCG/ ℓ , from bow	0.511	————→
B/H	2.50	————→
ℓ/B	7.5	————→
ℓ/H	18.75	————→
Rudder span, ft	0.200	0
Rudder chord, ft	0.105	0

Lamb's Coefficients of Accession to Inertia for Equivalent Ellipsoid

Minor axis/major axis, $2H/\ell$	0.107	————→
k_1 (longitudinal)	0.022	————→
k_2 (lateral)	0.957	————→
k' (rotational)	0.875	————→

Other Physical Characteristics

m'_0 , mass coefficient	0.159	————→
m'_1 , longitudinal added-mass coefficient	0.003	————→
m'_2 , lateral added-mass coefficient	0.156	————→
m'_z , rotational added-mass coefficient	0.143	————→
n'_z , virtual moment-of-inertia coefficient	0.019	————→
\bar{x}/ℓ , CG of lateral added mass from LCG	0.022	————→
x_p/ℓ , center of area of profile from LCG	0.027	————→
D'_0 (estimated drag coefficient at $\beta = 0$)	0.017	————→
σ_1 , calculated from theoretical derivatives	-0.62	-0.17
σ_1 , calculated from experimental rates	-0.55	-0.17




FIGURE C-1. BODY PLAN OF EXTREME VEE MODIFICATION OF SERIES 60.

(MODEL 9)

R-1035




FIGURE C-2. SERIES 60, MODEL 9,1,1. TOTAL LATERAL FORCE COEFFICIENT





FIGURE C-3. SERIES 60, MODEL 9.1.1. YAWING MOMENT COEFFICIENT





FIGURE C-4. SERIES 60, MODEL 9,00. TOTAL LATERAL FORCE COEFFICIENT





FIGURE C-5. SERIES 60, MODEL 90.0. YAWING MOMENT COEFFICIENT

BLANK PAGE

R-1035

APPENDIX D

MARINER CLASS HULL

(Reference 5)

TABLE D-1

PERTINENT CHARACTERISTICS OF THE MARINER CLASS MODEL

Length ℓ , ft (LWL)	5.0
Beam B, ft	0.731
Draft H , ft (mean)	0.236
Displacement Δ , lb	32.6
Prismatic coefficient, $C_p = 2x_o/\ell$	0.620
Block coefficient C_B	0.607
LCG/ ℓ , from bow	0.524
B/H	3.10
ℓ/B	6.84
ℓ/H	21.19

Lamb's Coefficients of Accession to Inertia for Equivalent Ellipsoid

Minor axis/major axis, $2H/\ell$	0.094
k_1 (longitudinal)	0.02
k_2 (lateral)	0.96
k^1 (rotational)	0.89

Other Physical Characteristics

m'_0 , mass coefficient	0.177
m'_1 longitudinal added-mass coefficient	0.003
m'_2 lateral added-mass coefficient	0.136
m'_z rotational added-mass coefficient	0.126
n'_z virtual moment-of-inertia coefficient	0.019
\bar{x}/ℓ , CG of lateral added mass from LCG	0.066
x_p/ℓ , center of area of profile from LCG	0.058
D'_0 (estimated drag coefficient at $\beta = 0$)	0.014

TABLE D-2
STABILITY DERIVATIVES FOR THE MARINER CLASS MODEL
(Without Propeller)

	Theoretical Estimate*	Experimental Range** (Ref. 16)
Y'_β	0.310	0.295 to 0.218
N'_β	0.068	0.066 to 0.122
$Y'_{r'}$	0.065	0.066 to 0.055
$N'_{r'}$	-0.059	-0.050 to -0.037
m'_2 = lateral added-mass coefficient	0.136	0.114 to 0.151
$n'_z - \frac{m'_0}{16}$ = added moment-of- inertia coefficient	0.008	0.007
σ_1	-0.49	-0.42 (best) -0.16 (average)

*Also, as shown on the charts, a reasonable fit to the Davidson Laboratory rotating-arm experimental data.

**Oscillator results nondimensionalized according to the convention adopted in the present paper.

BLANK PAGE




FIGURE D-1. BODY PLAN OF MARINER CLASS MODEL




FIGURE D-2. MARINER CLASS. FORCE AND MOMENT COEFFICIENTS VERSUS $r' = l/R$




FIGURE D-3. MARINER CLASS. TOTAL LATERAL FORCE COEFFICIENT VERSUS YAW ANGLE β .




FIGURE D-4. MARINER CLASS. YAWING MOMENT COEFFICIENT VERSUS YAW ANGLE β

R-1035

APPENDIX E

DESTROYER MODEL
(Reference 6)

TABLE E-1
PERTINENT CHARACTERISTICS OF THE DD692 DESTROYER MODEL

Length ℓ , ft	5.710
Beam B , ft	0.602
Draft H , ft	0.208
Displacement Δ , lb	25.22
Prismatic coefficient, $C_p = 2x_o/\ell$	0.643
Block coefficient, C_B	0.566
LCG/ ℓ , from bow	0.522
B/H	2.90
ℓ/B	9.45
ℓ/H	27.40

Lamb's Coefficients of Accession to Inertia for Equivalent Ellipsoid

Minor axis/major axis, $2H/\ell$	0.073
k_1 (longitudinal)	0.015
k_2 (lateral)	0.972
k' (rotational)	0.920

Other Physical Characteristics

m'_o , mass coefficient	0.119
m'_1 longitudinal added-mass coefficient	0.002
m'_2 lateral added-mass coefficient	0.087
m'_z rotational added-mass coefficient	0.082
n'_z virtual moment-of-inertia coefficient	0.0122
\bar{x}/ℓ , CG of lateral added mass from LCG	0.070
x_p/ℓ , center of area of profile from LCG	0.054
D'_o , drag coefficient at $\beta = 0$, $U = 2.1$ ft/sec	0.017
σ_1 stability index	-0.76




FIGURE E-1. BODY PLAN OF DD 692 DESTROYER MODEL




FIGURE E-2. DD 692 DESTROYER. TOTAL LATERAL FORCE COEFFICIENT




FIGURE E-3. DD 692 DESTROYER. YAWING MOMENT COEFFICIENT

BLANK PAGE

R-1035

APPENDIX F

HOPPER-DREDGE MODELS

(Reference 7)

TABLE F-1
PERTINENT CHARACTERISTICS OF THE HOPPER-DREDGE MODEL

<u>Condition</u>	<u>Heavy</u>	<u>Light</u>
Length ℓ , ft (LWL)	4.333	4.167
Beam B, ft	0.721	0.721
Draft H, ft	0.299	0.208
Displacement Δ , lb	41.65	32.08
Prismatic coefficient, $C_p = 2x_o/\ell$	0.727	0.840
Block coefficient C_B	0.717	0.820
LCG/ ℓ , from bow	0.500	0.512
B/H	2.415	3.461
ℓ/B	6.00	5.78
ℓ/H	14.51	20.00

Lamb's Coefficients of Accession to Inertia for Equivalent Ellipsoids

Minor axis/major axis, $2H/\ell$	0.138	0.100
k_1 (longitudinal)	0.033	0.020
k_2 (lateral)	0.936	0.960
k' (rotational)	0.815	0.885

Other Physical Characteristics

m_o' , mass coefficient	0.239	0.284
m_1' , longitudinal added-mass coefficient	0.008	0.006
m_2' , lateral added-mass coefficient	0.237	0.171
m_z' , rotational added-mass coefficient	0.207	0.158
n_z' , virtual moment of inertia	0.0315	0.0311
\bar{x}/ℓ , CG of lateral added mass from LCG	0.021	0.013
x_p/ℓ , center of area of profile from LCG	0.016	0.014
D_o' (drag coefficient at $\beta = 0$)	0.025	0.028

TABLE F-2
 STABILITY INDEX σ_1 FOR THE HOPPER-DREDGE MODEL

<u>Condition</u>	<u>Model Speed ft/sec</u>	<u>σ_1 Theoretical Estimate</u>	<u>Calculated from Measurements (Ref.7)</u>
Heavy	2.39	+0.83	+0.89
	1.40	+0.83	+1.04
Light	1.80	+0.60	+0.82

BLANK PAGE




FIGURE F-1. BODY PLAN OF HOPPER DREDGE MODEL





FIGURE F-2. HOPPER DREDGE, HEAVY DISPLACEMENT.
TOTAL LATERAL FORCE COEFFICIENT





FIGURE F-3. HOPPER DREDGE, HEAVY DISPLACEMENT, YAWING MOMENT COEFFICIENT





FIGURE F-4. HOPPER DREDGE, LIGHT DISPLACEMENT.
TOTAL LATERAL FORCE COEFFICIENT





FIGURE F-5. HOPPER DREDGE, LIGHT DISPLACEMENT. YAWING MOMENT COEFFICIENT

BLANK PAGE

DISTRIBUTION LIST
Contract Nonr 263(57)

Copies

10 Chief
 BUREAU OF SHIPS
 Department of the Navy
 Washington 25, D. C.
 Attn Tech. Info. Br. (Code 335) (3)
 Res. & Devel. (Code 310) (1)
 Prelim. Design (Code 420) (1)
 Prelim. Design (Code 421) (1)
 Hull Design Br. (Code 440) (1)
 Scien. & Res. (Code 442) (1)
 (Code 341B) (1)
 (Code 345) (1)

75 Commanding Officer and Director
 DAVID TAYLOR MODEL BASIN
 Washington 7, D. C.
 Attn (Code 513)

20 DEFENSE DOCUMENTATION CENTER
 Cameron Station
 5010 Duke St.
 Alexandria, Va. 22314

1 Chief of NAVAL RESEARCH
 Fluid Dynamics Branch
 Department of the Navy
 Washington 25, D. C.
 Attn (Code 438)

1 Commanding Officer
 OFFICE OF NAVAL RESEARCH
 Branch Office
 230 N. Michigan Ave.
 Chicago 1, Ill.

1 Commanding Officer
 OFFICE OF NAVAL RESEARCH
 207 West 24th St.
 New York 11, N. Y.

1 Commanding Officer
 OFFICE OF NAVAL RESEARCH
 Branch Office
 1030 East Green St.
 Pasadena 1, Calif.

Copies

1 Commanding Officer
 OFFICE OF NAVAL RESEARCH
 Branch Office
 1000 Geary Street
 San Francisco 9, California

1 Commander
 BOSTON NAVAL SHIPYARD
 Boston, Massachusetts

1 Commander
 CHARLESTON NAVAL SHIPYARD
 Charleston, South Carolina

1 Administrator
 Maritime Administration
 DEPARTMENT OF COMMERCE
 Washington 25, D. C.
 Attn Office of Ship Construction
 Mr. Vito L. Russo

1 Office of Technical Services
 DEPARTMENT OF COMMERCE
 Washington 25, D. C.
 Attn Technical Reports Sec.

2 Chief
 BUREAU OF WEAPONS
 Department of the Navy
 Washington 25, D. C.

1 Chief
 BUREAU OF YARDS & DOCKS
 Department of the Navy
 Washington 25, D. C.
 Attn Code D-400 Research Div.

1 Commander
 Military Sea Transportation
 DEPARTMENT OF THE NAVY
 Washington 25, D. C.

1 Commander
 LONG BEACH NAVAL SHIPYARD
 Long Beach, California

DISTRIBUTION LIST
Contract Nonr 263(57)

Copies

- 1 Commander
MARE ISLAND NAVAL SHIPYARD
Vallejo, California
- 1 Director
NAT'L AERONAUTICS & SPACE ADM.
1512 H Street, N.W.
Washington 25, D. C.
- 1 Director
NATIONAL BUREAU OF STANDARDS
Washington 25, D. C.
Attn Dr. G. B. Schubauer
Fluid Mechanics
- 1 Director
NATIONAL SCIENCE FOUNDATION
1420 H Street, N.W.
Washington, D. C.
- 6 Director
NAVAL RESEARCH LABORATORY
Washington 25, D. C.
Attn (Code 2021) Library
- 1 Commander
NEW YORK NAVAL SHIPYARD
Brooklyn, New York
- 1 Commander
NORFOLK NAVAL SHIPYARD
Portsmouth, Virginia
- 1 Commander
PEARL HARBOR NAVAL SHIPYARD
Navy #128, Fleet Post Office
San Francisco, California
- 1 Director
PHILADELPHIA NAVAL SHIPYARD
Philadelphia, Pennsylvania
- 1 Commander
PORTSMOUTH NAVAL SHIPYARD
Portsmouth, New Hampshire

Copies

- 1 Commander
PUGET SOUND NAVAL SHIPYARD
Bremerton, Washington
- 1 Commander
SAN FRANCISCO NAVAL SHIPYARD
San Francisco, California
- 1 U.S. ARMY TRANS. RESEARCH &
ENGINEERING COMMAND
Fort Eustis, Virginia
Attn Marine Transport Div.
- 2 U.S. COAST GUARD
1300 E Street, N.W.
Washington 25, D. C.
Attn Sec., Ship Structure
Commandant
- 1 Superintendent
U.S. MERCHANT MARINE ACADEMY
Kings Point, L.I., New York
Attn Capt. L. McCready, Head
Dept. of Engineering
- 1 U.S. NAVAL ACADEMY
Annapolis, Maryland
Superintendent
Attn Library
- 1 U.S. NAVAL POST GRADUATE SCHOOL
Monterey, California
Attn Superintendent
- 1 Commander
U.S. NAVAL PROVING GROUND
Dahlgren, Virginia
- 1 Commander
U.S. NAVAL SHIP REPAIR FACILITY
San Diego, California
- 1 AERONAUTICAL RESEARCH ASSOCIATES
OF PRINCETON, INC.
50 Washington Road
Princeton, New Jersey
Attn Dr. Bernard Paiewonsky

DISTRIBUTION LIST
Contract Nonr 263(57)

Copies

- 1 Mr. Walter J. Blumberg
U.S. NAVAL MARINE ENGINEERING
LABORATORY
Annapolis, Maryland
Attn Code 812.8
- 1 CALIFORNIA INST. OF TECHNOLOGY
Pasadena 4, California
Attn Prof. T. Y. Wu
- 3 COLORADO STATE UNIVERSITY
Dept. of Civil Engineering
Fort Collins, Colorado
Attn Prof. M. Albertson
Prof. J. Cermak
Prof. L. V. Baldwin
- 1 CORNELL AERONAUTICAL LAB., INC.
Applied Mechanics Dept.
P. O. Box 235
Buffalo 21, New York
Attn Dr. Irving C. Statler
- 1 DARTMOUTH COLLEGE
Thayer School of Engineering
Hanover, New Hampshire
Attn Prof. Sidney Lees
- 2 DOUGLAS AIRCRAFT CO., INC.
Aircraft Division
Long Beach, California
Attn Mr. John Hess
Mr. A. M. O. Smith
- 2 Electric Boat Division
GENERAL DYNAMICS CORPORATION
Groton, Connecticut
Attn Mr. H. E. Sheets
Mr. R. J. McGrattan
- 1 HYDRONAUTICS, INCORPORATED
Pindell School Road
Howard County, Laurel, Md.
Attn Mr. Phillip Eisenberg

Copies

- 1 HYDRO SPACE ASSOCIATES
3775 Sheridge Drive
Sherman Oaks, California
Attn Dr. Leonard Pode
- 2 Courant Inst. of Math. Sciences
NEW YORK UNIVERSITY
25 Waverly Place
New York 3, New York
Attn Prof. J. Stoker
Prof. A. Peters
- 1 PENNSYLVANIA STATE UNIVERSITY
University Park, Pennsylvania
Attn Ordnance Research Lab.
Director
- 1 Ordnance Research Laboratory
PENNSYLVANIA STATE UNIVERSITY
P. O. Box 30
University Park, Pennsylvania
Attn Dr. George F. Wislicenus
- 1 ROBERT TAGGART, INC.
400 Arlington Blvd.
Falls Church, Virginia
Attn Mr. Robert Taggart
- 1 Dr. Karl E. Schoenherr
7053 Western Ave., N.W.
Washington, D. C 20015
- 1 SOCIETY OF NAVAL ARCHITECTS
AND MARINE ENGINEERS
74 Trinity Place
New York 6, New York
- 1 SOUTHWEST RESEARCH INSTITUTE
Dept. of Mechanical Sciences
8500 Culebra Road
San Antonio 6, Texas
Attn Dr. H. Norman Abramson

DISTRIBUTION LIST
Contract Nonr 263(57)

Copies

- 2 Iowa Inst. of Hydraulic Research
STATE UNIVERSITY OF IOWA
Iowa City, Iowa
Attn Prof. H. Rouse, Director
Prof. L. Landweber
- 1 Maritime College
STATE UNIVERSITY OF NEW YORK
Fort Schuyler
New York 65, New York
Attn Engineering Dept.
Prof. J. J. Foody
- 1 MASS. INST. OF TECHNOLOGY
Cambridge 39, Massachusetts
Attn Prof. J. E. Kerwin
Dept. of Naval Arch. &
Marine Engineers
- 1 MASS. INST. OF TECHNOLOGY
Cambridge 39, Massachusetts
Attn Dr. E. Covert
Aerophysics Laboratory
- 1 MASS. INST. OF TECHNOLOGY
Cambridge 39, Massachusetts
Attn Dr. H. L. Moses
Gas Turbine Laboratory
- 2 MASS. INST. OF TECHNOLOGY
Cambridge, Massachusetts 02139
Attn Dept. of Naval Arch. &
Marine Engineers
Prof. L. Troost, Head
Prof. Philip Mandel
- 2 NEW YORK UNIVERSITY
University Heights
New York 53, New York
Attn Dept. of Oceanography
Prof. W. J. Pierson, Jr.
- 1 TECHNICAL RESEARCH GROUP, INC.
Route 110
Melville, L.I., New York
Attn Dr. Jack Kotik

Copies

- 3 UNIVERSITY OF CALIFORNIA
Berkeley 4, California
Attn College of Engineering
Prof. H. A. Schade
Prof. J. Johnson
Prof. J. V. Wehausen
- 1 UNIVERSITY OF ILLINOIS
College of Engineering
Dept. of Theoretical &
Applied Mechanics
Urbana, Illinois
Attn Prof. J. M. Robertson
- 1 UNIVERSITY OF MARYLAND
College Park, Maryland
Attn Institute for Fluid Dynamics
and Applied Mathematics
- 2 UNIVERSITY OF MICHIGAN
Dept. of Naval Arch. & Marine
Engineers
Ann Arbor, Michigan
Attn Prof. R. B. Couch, Head
Dr. Finn C. Michelsen
- 2 UNIVERSITY OF MINNESOTA
St. Anthony Falls Hydraulic Lab
Minneapolis 14, Minnesota
Attn Prof L. G. Straut
- 1 VIDYA
1450 Page Mill Road
Palo Alto, California
Attn Dr. A. H. Sacks
- 1 VIRGINIA POLYTECHNIC INST.
Blacksburg, Virginia
Attn Librarian
- 1 WEBB INST. OF NAVAL ARCHITECTURE
Crescent Beach Road
Glen Cove, L. I., New York
Administrator
Attn Technical Library
- 1 WOODS HOLE OCEANOGRAPHIC INST.
Woods Hole, Massachusetts
Attn Dr. C. Iselin

amics
s

BLANK PAGE

ab.

URE

.

<p>DAVIDSON LABORATORY Report 1035 (UNCLASSIFIED) Sept. 1964</p> <p>ESTIMATION OF STABILITY DERIVATIVES AND INDICES OF VARIOUS SHIP FORMS, AND COMPARISON WITH EXPERIMENTAL RESULTS</p> <p>By Winnifred R. Jacobs</p> <p>Buships Fundamental Hydromechanics Research Program (S-R009-01-01) Administered by DTMB Contract Nonr 263(57) DL Project 2803/063</p> <p>The analytical method of Ref. 1 for estimating stability derivatives, and hence stability on course, which combines Albring's empirical modifications of simplified flow theory with low aspect-ratio wing theory, is extended to take into consideration the effects on course stability of higher aspect-ratio fins as well. The method, which had (over)</p>	<p>DAVIDSON LABORATORY Report 1035 (UNCLASSIFIED) Sept. 1964</p> <p>ESTIMATION OF STABILITY DERIVATIVES AND INDICES OF VARIOUS SHIP FORMS, AND COMPARISON WITH EXPERIMENTAL RESULTS</p> <p>By Winnifred R. Jacobs</p> <p>Buships Fundamental Hydromechanics Research Program (S-R009-01-01) Administered by DTMB Contract Nonr 263(57) DL Project 2803/063</p> <p>The analytical method of Ref. 1 for estimating stability derivatives, and hence stability on course, which combines Albring's empirical modifications of simplified flow theory with low aspect-ratio wing theory, is extended to take into consideration the effects on course stability of higher aspect-ratio fins as well. The method, which had (over)</p>
<p>DAVIDSON LABORATORY Report 1035 (UNCLASSIFIED) Sept. 1964</p> <p>ESTIMATION OF STABILITY DERIVATIVES AND INDICES OF VARIOUS SHIP FORMS, AND COMPARISON WITH EXPERIMENTAL RESULTS</p> <p>By Winnifred R. Jacobs</p> <p>Buships Fundamental Hydromechanics Research Program (S-R009-01-01) Administered by DTMB Contract Nonr 263(57) DL Project 2803/063</p> <p>The analytical method of Ref. 1 for estimating stability derivatives, and hence stability on course, which combines Albring's empirical modifications of simplified flow theory with low aspect-ratio wing theory, is extended to take into consideration the effects on course stability of higher aspect-ratio fins as well. The method, which had (over)</p>	<p>DAVIDSON LABORATORY Report 1035 (UNCLASSIFIED) Sept. 1964</p> <p>ESTIMATION OF STABILITY DERIVATIVES AND INDICES OF VARIOUS SHIP FORMS, AND COMPARISON WITH EXPERIMENTAL RESULTS</p> <p>By Winnifred R. Jacobs</p> <p>Buships Fundamental Hydromechanics Research Program (S-R009-01-01) Administered by DTMB Contract Nonr 263(57) DL Project 2803/063</p> <p>The analytical method of Ref. 1 for estimating stability derivatives, and hence stability on course, which combines Albring's empirical modifications of simplified flow theory with low aspect-ratio wing theory, is extended to take into consideration the effects on course stability of higher aspect-ratio fins as well. The method, which had (over)</p>

BLANK PAGE

<p>been applied in the earlier report to a family of eight hulls of 0.5 block coefficient, is tested further by application to eight Series 60 forms differing in block coefficient as well as in beam, draft, and displacement – with and without rudders; to an extreme vee modification of a Series 60 model; and to three other forms – a Mariner Class model, a destroyer, and a hopper dredge. Comparison with experimental results shows that the values of stability derivatives and indices determined by the analytical method are of the right orders of magnitude and indicate correct trends. Application to a variety of ship forms has demonstrated that the method can predict relative effects of changes in the geometry of a ship form, as well as the effects of changes in skeg and rudder area.</p> <p>Keywords: Hydrodynamics, Maneuvering, Controllability</p>	<p>been applied in the earlier report to a family of eight hulls of 0.5 block coefficient, is tested further by application to eight Series 60 forms differing in block coefficient as well as in beam, draft, and displacement – with and without rudders; to an extreme vee modification of a Series 60 model; and to three other forms – a Mariner Class model, a destroyer, and a hopper dredge. Comparison with experimental results shows that the values of stability derivatives and indices determined by the analytical method are of the right orders of magnitude and indicate correct trends. Application to a variety of ship forms has demonstrated that the method can predict relative effects of changes in the geometry of a ship form, as well as the effects of changes in skeg and rudder area.</p> <p>Keywords: Hydrodynamics, Maneuvering, Controllability</p>
<p>been applied in the earlier report to a family of eight hulls of 0.5 block coefficient, is tested further by application to eight Series 60 forms differing in block coefficient as well as in beam, draft, and displacement – with and without rudders; to an extreme vee modification of a Series 60 model; and to three other forms – a Mariner Class model, a destroyer, and a hopper dredge. Comparison with experimental results shows that the values of stability derivatives and indices determined by the analytical method are of the right orders of magnitude and indicate correct trends. Application to a variety of ship forms has demonstrated that the method can predict relative effects of changes in the geometry of a ship form, as well as the effects of changes in skeg and rudder area.</p> <p>Keywords: Hydrodynamics, Maneuvering, Controllability</p>	<p>been applied in the earlier report to a family of eight hulls of 0.5 block coefficient, is tested further by application to eight Series 60 forms differing in block coefficient as well as in beam, draft, and displacement – with and without rudders; to an extreme vee modification of a Series 60 model; and to three other forms – a Mariner Class model, a destroyer, and a hopper dredge. Comparison with experimental results shows that the values of stability derivatives and indices determined by the analytical method are of the right orders of magnitude and indicate correct trends. Application to a variety of ship forms has demonstrated that the method can predict relative effects of changes in the geometry of a ship form, as well as the effects of changes in skeg and rudder area.</p> <p>Keywords: Hydrodynamics, Maneuvering, Controllability</p>

BLANK PAGE